

# Edit Group - Multiple Values Template

Version 2

Published 4/17/2018 12:31 AM by [Grace Kamau](#) Last updated 4/17/2018 07:30 PM by [Grace Kamau](#)

This template is for a [Field Group](#) that permits multiple values.

Education +1

School	Graduation date
<input type="text" value="School"/>	<input type="text" value="Graduation date"/>

```
<div class="axero-group-field-multiple ax-form-field {{CustomCSSClass}} {{#if HideContainerBorder}}axero-widget-no-border{{/if}} {{#if WidgetStub}} id="section-{{WidgetStub}}"{/if}} pb-field data-fieldid="{{Contents.FieldUseID}}">
<div class="axero-widget-header">
<button class="btn btn-small pb-plus-one hide" type="button" data-fieldid="{{Contents.FieldUseID}}" ng-plus-one+1</button>
{{#if ShowWidgetHeader}}
{{#if ShowWidgetHeader}}<label>{{WidgetTitle}}</label>{{#if Contents.Field.NumRequired}}&nbsp;&nbsp;&nbsp;<span class="loud red">*</span>{{/if}}</div>
<div class="axero-group-field-list">
<div ng-show="values.length > 1" ng-repeat="groupField{{Contents.FieldUseID}} in values = (fields | fieldFilter:{{Contents.FieldUseID}})"
ng-class="{active: groupField{{Contents.FieldUseID}}.ActiveSet == true}"
ng-click="editFieldGroup({{Contents.FieldUseID}}, groupField{{Contents.FieldUseID}}.DataID)">
<i ng-click="removeValue({{Contents.FieldUseID}}, groupField{{Contents.FieldUseID}}.DataID)" class="icon-remove-sign"></i>
<span ng-bind-html="groupField{{Contents.FieldUseID}}.FieldValue | {{Resources.NoSummaryAvailableText}}"></span>
</div>
</div>
</div>
<div class="axero-group-field-child-fields" ng-show="groupField{{Contents.FieldUseID}}.ActiveSet" ng-repeat="groupField{{Contents.FieldUseID}} in values = (fields | fieldFilter:{{Contents.FieldUseID}})"
<i ng-show="values.length > 1" ng-click="editFieldGroup({{Contents.FieldUseID}})" class="icon-chevron-up collapse-field-group"></i>
{{Contents.ChildWidgetHTML}}
</div>
{{#if ShowWidgetFooter}}
<div class="axero-widget-footer">
</div>
{{/if}}
</div>
```

tags : site-administrator