

REST API: Mark Message As Read

Version 6

Published 1/5/2019 12:00 PM by [Anonymous User](#) Last updated 8/31/2020 10:07 PM by [Grace Kamau](#)

Mark Message As Read

PUT /api/chat/threads/readstatus

Mark message as read. Valid for Communifire version 6.0 and above.

Method Details

HTTP Method

PUT

Response Format

JSON

Requires Authentication?

YES

Product Version

6.0 and above

Required Parameters	How to use	Description
API Key	Used in the request URL: &token=x OR Set in header: request.Headers.Add(Rest-API-Key, x)	Communifire REST API key for the Communifire portal you are making the call for.
Message JSON	Used in the request body	This is JSON that represents a chat object that you're creating. This should be of the format seen below in the sample given. The required values in this JSON are given below.
ThreadIDCSV	Used in the request body	Unique identifier for a particular thread.

Example URL: <https://your-community.com/api/chat/threads/readstatus>

Request JSON sample for marking message as read

```
{
  "threadIDCSV": "1"
}
```

Response JSON sample where indicator (1- True, 0- False) is returned as ResponseData

Here is an example of JSON data returned from the API call.

```
{
  "IsError":false,
  "ResponseMessage":"",
  "ResponseData":1
}
```

Please Note Your content type that you pass in the header of your request should be **'application/json'**.

tags : API