REST API: Set Content Status

Version 35

Published 3/31/2011 11:42 AM by Vivek Thakur Last updated 10/1/2020 11:26 PM by Grace Kamau

---

Set Content Status

PUT /api/content/{ContentID}/status

Set the publication status of existing content. List of supported entities: Articles, Blogs, CMS Pages, Wikis, Files, Videos, Ideas, Photos, Albums, Forums, Forum Groups, Forum Topics, Forum Posts. Valid for Communifire version 5.2 and above.

Method Details

HTTP Method

PUT

Response Format

JSON

Requires Authentication?

YES

Product Version

5.2 and above

Required Parameters	How to use	Description
API Key	Used in the request URL: &token=x OR Set in header: request.Headers.Add(Rest-Api-Key, x)	Communifire REST API key for the Communifire portal you are making the call for.
ContentID	Used in the request URL as a path parameter	Unique identifier for a particular content. List of supported entities: Articles, Blogs, CMS Pages, Wikis, Files, Videos, Ideas, Photos, Albums, Forums, Forum Groups, Forum Topics, Forum Posts.
StatusID	Used in the request body	Status of the content. Here are the values of Entity Status parameter: • Published = 1 • Declined = 3 • Deleted = 11

Example Request

PUT https://myintranet.communifire.com/api/content/2304/status

Body:

```
1
```

Example Response

True/false is returned as ResponseData.

```
{
    "IsError":false,
    "ResponseMessage":"",
    "ResponseData":"True"
}
```

Please Note The content type that you pass in the header of your request should be **application/json**.

tags : API